


ZEP MANUFACTURING COMPANY P.O. BOX 2015 ATLANTA: GEORGIA 30301 1-877-I-BUY-ZEP (1-877-428-9937)



MATERIAL SAFETY DATA SHEET AND SAFE HANDLING AND DISPOSAL INFORMATION

ISSUE DATE:

11/13/00

SUPERSEDES:

05/08/92

Date printed: 01/24/01

ZEP FORMULA 6556 Product No:

1093

Acid Mason y Cleaner

SECTION I -EMERGENCY CONTACTS

For a Medical Emergency:

(877)541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency:

(800)424-9300 Toll Free - All Calls Recorded

EFFECTS (SEE NOTICE) % IN PROD. SECTION II - HAZARDOUS INGREDIENTS TLV (PPM) DESIGNATIONS 5 25-35 @**#HYDROCHEORIGIACID.** (munanciacid: hydrogen; chloride: hydrochloride; CAS# 7647-01-0; RTECS# MW4025000; OSHA/ACGIH TOX COR

CEILING LIMIT-5 PPM

@ IDENTIFIES CHEMICALS LISTED UNDER SARA-SECTION 313 FOR RELEASE REPORTING.

SECTION III - HEALTH HAZARD DATA

SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use (diluted) so long as prescribed safety precautions are practiced.

ACUTE EFFECTS OF OVEREXPOSURE:

Corrosive to skin and eyes on contact. Eye contact can produce corneal damage or blindness. Skin contact can produce inflammation, reddening, and blistering. Inhalation of spray mist or vapors may produce irritation, urning, or destruction of tissues in the respiratory tract, characterized by coughing choking, pain, or

shortness of breath. Severe overexposure may lead to fatal lung damage. Ingestion can cause abdominal pain, nausea, vomiting, and collapse, along with tissue destruction in the gastrointestinal tract.

CHRONIC EFFECTS OF OVEREXPOSURE:

Repeated or prolonged contact with acid vapors may cause nasal ulceration, bronchial irritation and frequent attacks of bronchial infection. In extreme cases, teeth erosion could result. Repeated or prolonged exposure to vapors may cause chronic eye irritation or frequent eye infections.

Ingredients in this product may aggravate existing skin, eye, or respiratory disorders. None of the hazardous ingredients are listed as carcinogens by IARC, NTP, & OSHA

PRIMARY ROUTES OF ENTRY: Inh. Skin. EST'D PEL/TLV: Not established

HMIS CODES: HEALTH 3; FLAM. 0; REACT. 1; PERS. PROTECT. 🗶 ; CHRONIC HAZ. YES 🍾

FIRST AID PROCEDURES:

SKIN: Immediately flush contaminated skin with plenty of water for at least 15 minutes. Get medical attention immediately.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and

lower lids. Get medical attention at once.

INHALE: Move exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Get medical attention immediately.

INGEST: If this product is swallowed, do not induce vomiting. If individual is alert, give plenty of water to drink. Get medical attention at once.

SECTION IV - SPECIAL PROTECTION INFORMATION

PROTECTIVE CLOTHING: Wear rubber gloves, a rubber rainsuit, and rubber boots when using this product or when working in a use area.

EYE PROTECTION: Use tight-fitting, splash-proof safety goggles. Contact lenses should not be worn when handling this material.

RESPIRATORY PROTECTION: When exposure levels exceed PEL/TLV, use ZEP Model 2245 respirator (or

quivalent) as directed by manufacturer. VENTILATION: Provide local exhaust/ventilation as needed to keep concentration of vapors below exposure llimits (PEL/TLV).

(Continued on Page: 2)

1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1			3.14-0.15.51	
ZEP MANUFACTURING CON	IPANY MATERIAI	L SAFERY DATA SHEET		PAGE: 2
Product No: 1093 BOILING POINT (F): VAPOR PRESSURE(mmHg): VAPOR DENSITY(AIR = 1): OLUBILITY IN WATER: DOLGONTENT (CONCENTRAPPEARANCE AND ODOR: A	N/A COMPLETE (0.0% 0.00 lb/g BROWN LIQUID WITH S	SPECIFIC GRAVITY: EVAPORATION RAT pH(CONCENTRATE) pH(USE DILUTION C gl STRONG, IRRITATING ACIDI	E (WATER = 1): : PF 1% SOLUTION):	1.13 1.0 < 1.0 1.0-2.0
FLASH POINT(F) (METHOD)U FLAMMABLE LIMITS: LEL: N. EXTINGUISHING MEDIA: No SPECIAL FIRE FIGHTING: We UNUSUAL FIRE HAZARDS: N	SECTION VI - FIRE A SED): None A UEL: N/A combustible. ar self-contained positive	ND EXPLOSION DATA (TCC) pres. breathing apparatus.		
	SECTION VII - REACT	TIVITY DATA		
STABILITY: Stable INCOMPATIBLILITY(AVOID): POLYMERIZATION: Will not o HAZARDOUS DECOMPOSITION	ccur.	•		
STEPS TO BE TAKEN IN CAS Observe safety precautions in (e.g. Zep-O-Zorb); pick up and thoroughly with a detergent s	E MATERIAL IS RELEASE sections 4 & 9 during cl d place in a clean D.O. T. olution and then rinse we	ean-up. Absorb spill on an i specification container for o	inert absorbent materia	ıl
WASTE DISPOSAL METHOD: Liquids cannot be sent to land use-dilutions may require disp most states hazardous waste or industrial waste landfill. If neutralization of spent tank-so state and federal agencies for RCRA HAZ. WASTE NOS.: Do	ifills unless solidified. Unicosal as a hazardous wasts in total amounts of 220 company effluent is ultimolutions with subsequent proper disposal method in	te at a permitted treatment/s Ibs. or less per month may ately treated by a publicly o discharge to the sewer may	storage/disposal facility be disposed of in a ch wned treatment works	emical ,
PRECAUTIONS TO BE TAKEN Store tightly closed container Store away from highly alkali Do not breathe spray mists of Keep away from food and foo Clothing or shoes which beco thoroughly cleaned. Keep out of the reach of child	in a dry area at temps. b ne products and oxidizing vapors. od products. me contaminated with su	STORING: etween 40-120 degrees F. compounds.	promptly and not rew	orn until
DOT PROPER SHIPPING NAM (HYDROCHLORIC ACID) NOTE: DOT information application application application application and land the control of the	IE: CORROSIVE LIQUID, And to larger package sizes abeling in accordance with DOT DOT LABEL/PLACARD: TORY - ALL INGREDIENT SUBSTANCE(RQ IN A SIMOMERS:	of affected products. For some packaging group requiremed PACKING GROUP: If CORROSIVE S ARE LISTED NGLE CONTAINER): HYDRO	ome products, DOT materials \mathbf{i}^{l}	a y
·	·			

ZEP MANUFACTURING COMPANY MATERIAL SAFETY DATA SHEET Page 3

** NOTICE **

Thank you for your interest in, and use of, Zep products.

Zep Manufacturing Co. is pleased to be of service to you by supplying this Material Safety Data Sheet for your files. Zep Manufacturing is concerned for your health and safety. Zep oducts can be used safely with proper protective equipment d proper handling practices consistent with label instructions ... id the MSDS. Before using any Zep product, be sure to read the complete label and the Material Safety Data Sheet. ** NOTICE **

As a further word of caution, Zep wishes to advise that serious accidents have resulted from the misuse of "emptied" containers. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, fiame, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Clean empty containers by triple rinsing with water or an appropriate solvent. Empty containers must be sent to a drum reconditioner before reuse.

TERMS AND ABBREVIATIONS LISTED ALPHABETICALLY BY SECTION

SECTION II: HAZARDOUS INGREDIENTS
CAR; Carcinogen - A chemical listed by the National Toxicology
Program (NTP), the International Agency for Research on Cancer
(IARC) or OSHA as a definite or possible human cancer causing

agent.
CAS #; Chemical Abstract Services Registry Number - A universally accepted numbering system for chemical substances.
CBL; Combustible - At temperatures between 100F and 200F chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.
CNS; Central Nervous System depressant reduces the activity of the harin and spiral cond

of the brain and spinal cord. COR; Corrosive - Causes irreversible injury to living

tissue (e.g. burns).
DESIGNATIONS; Chemical and common names of hazardous ingredients.

EIR; Eye Irritant Only - Causes reversible reddening and/or

BIK; Bye Ifficant Only - Causes reversible reddening and/or inflammation of eye tissues.

EXPOSURE LIMITS; The time weighted average (TWA) airborne concentration at which most workers can be exposed without any prected adverse effects. Primary sources include ACGIH TLVs, and OSHA PELs (TWA, STEL and ceiling limits).

ACGIH; American Conference of Governmental Industrial

ACGIH; American Contenence of Governmental Industrial Hygienists.
CEILING; The concentration that should not be exceeded in the workplace during any part of the working exposure.
OSHA; Occupational Safety and Health Administration PEL; Permissible Exposure Limit - A set of time weighted average exposure values, established by OSHA, for a normal 8-hour day and a 40-hour work week.
PPM; Parts per million - unit of measure for exposure limits.
(S) SKIN; Skin contact with substance can contribute to overall exposure.

overall exposure.

overall exposure.

STEL; Short Term Exposure Limit - Maximum concentration for a continuous 15-minute exposure period.

TLV; Threshold Limit Value - A set of time weighted average exposure limits, established by the ACGIH, for a normal 8-hour day and a 40-hour work week.

FBL; Flammable - At temperatures under 100F, chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.

HAZARDOUS INGREDIENTS; Chemical substances determined to be potential health or physical hazards by the criteria established in the OSHA Hazard Communication Standard - 29 CFR 1910, 1200

HTX; Highly toxic - the probable lethal dose for a 70kg (150 lb.) man and may be approximated as less than 6 teaspoons (2 tablespoons).

IRR; Irritant - Causes reversible effects in living tissues (e.g. inflammation) - primarily skin and eyes.

N/A; Not Applicable - Category is not appropriate for this

product

N/D; Not Determined - Insufficient information for a RTECS#; Registry of Toxic Effects of Chemical Substances - an unreviewed listing of published toxicology data on chemical

substances.
SARA; Superfund Amendments and Reauthorization Act - Section 313 designates chemicals for possible reporting for the Toxics

.elease Inventory. SEN; Sensitizer - Causes allergic reaction after repeated

TOX; Toxic - The probable lethal dose for a 70 kg (150 lb.) man is one ounce (2 tablespoons) or more.

SECTION III: HEALTH HAZARD DATA
ACUTE EFFECT; An adverse effect on the human body from a single exposure with symptoms developing almost immediately after exposure or within a relatively short time.
CHRONIC EFFECT; Adverse effects that are most likely to occur from repeated exposure over a long period of time.
ESTD PEL/TLV; This estimated, time-weighted average, exposure limit, developed by using a formula provided by the ACGIH, pertains to airborne concentrations from the product as a whole. This value should serve as guide for providing safe workplace conditions to nearly all workers.
HMIS CODES; Hazardous Material Identification System - a rating system developed by the National Paint and Coating Association for estimating the hazard potential of a chemical under normal workplace conditions. These risk estimates are indicated by a numerical rating given in each of three hazard areas (Health/Flammability/reactivity) ranging from a low of zero to a high of 4. A chronic hazard is indicated with a yes.
Consult HMIS training guides for Personal Protection letter codes which indicate necessary protective equipment.
PRIMARY ROUTE OF ENTRY; The way one or more hazardous ingredients may enter the body and cause a generalized-systemic or specific-organ toxic effect.

ING; Ingestion - A primary route of exposure through swallowing of material
INH; Inhalation - A primary route of exposure through breathing of vapors.

SKIN: A primary route of exposure through contact with

breathing of vapors. SKIN; A primary route of exposure through contact with

the skin.

SECTION IV: SPECIAL PROTECTION INFORMATION Where respiratory protection is recommended, use only MSHA and NIOSH approved respirators and dust masks.

MSHA; Mine Safety and Health Administration
NIOSH; National Institute for Occupational Safety and Health

SECTION V: PHYSICAL DATA
EVAPORATION RATE; it refers to the rate of change from the liquid state to the vapor state at ambient temperature and pressure in comparison to a given substance (e.g. water).
pH; A value representing the acidity or alkalinity of an aqueous solution (Acidic pH = 1; Neutral pH = 7; Alkaline pH = 14)
VOC CONTENT; The percentage of or amount in pounds per gallon of the product that is regulated as a Volatile Organic Compound under the Clean Air Act of 1990 and various state invisitions jurisdictions.
SOLUBILITY IN WATER; A description of the ability of the product to dissolve in water.

SECTION VII: REACTIVITY DATA
HAZARDOUS DECOMPOSITION; Breakdown products expected to be
produced upon product decomposition or fire.
INCOMPATIBILITY; Material contact and the conditions to avoid
to prevent hazardous reactions.
POLYMERIZATION; Indicates the tendency of the product's
molecules to combine with themselves in a chemical reaction,
releasing excess pressure and heat.
STABILITY; Indicates the susceptibility of the product to
spontaneously and dangerously decompose.

SECTION VIII: SPILL AND DISPOSAL PROCEDURES RCRA WASTE NOS; RCRA (Resource Conservation and Recovery Act) waste codes (40 CFR 261) applicable to the disposal of spilled or unusable product from the original container.

SECTION X: TRANSPORTATION DATA
CWA; Clean Water Act- Federal Law which regulates chemical
releases to bodies of water.
RQ; Reportable Quantity - The amount of the specific ingredient
that, when spilled to the ground and can enter a storm sewer or
natural watershed, must be reported to the National Response
Center, and other regulatory agencies.
TSCA; Toxic Substances Control Act - a federal law requiring
all commercial chemical substances to appear on an inventory
maintained by the EPA.

DISCLAIMER

All statements, technical information and recommendations contained herein are based on available scientific tests or data which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with out products, may be used. Zep assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product's label and Material Safety Data Sheet.